

H5

Certifications

SYNTHÈSE
ACOUSTIQUE

ACOUSTIC
SYNTHESIS

Remplissages (mm)	Supplément	Isolant acoustique	Rw	Rw + C	n° PV
Fillings (mm)	Extra	Acoustic insulation			Certificate
H5					
Fermacel 12 + BF13 Fermacel 12 + plasterboards 13mm		30 mm	43	40	BPI2.7.6106-14
Fermacel 12 + Fermacel 15		30 mm	47	44	B212-6.818-7
33/2 + 6 mm		–	39	38	BEB2.F.6017-1
44/2 + 5 mm		–	41	39	BPI2.7.6106-11
Porte bois + plinthe automatique Wood door + automatic seal	Fermacel 12 + BF13 (plasterboards 13mm)	30 mm	32	31	BPI2.7.6106-15
H5JC (SUSPENDED PANELS)					
2 mélaminés 16 mm 2 melamineboards 16mm		60 mm	44	42	BEB2.H.6073-9
2 mélaminés 16 mm 2 melamineboards 16mm	TEC36	60 mm	47	45	BEB2.H.6073-10
2 mélaminés 19 mm 2 melamineboards 19mm		60 mm	46	45	BEB2.H.6073-11
2 mélaminés 19 mm 2 melamineboards 19mm	TEC36	60 mm	49	47	BEB2.H.6073-12

H5 | Certifications

Remplissages (mm)	Rw	Rw + C	n° PV
Fillings (mm)			Certificate
H5T			
55/2	34	32	BEB2.G.6072-8
55/2 silence	37	36	BEB2.G.6072-9
66/2 silence	38	38	BEB2.G.6072-10
55/2 + 10 mm	38	37	BEB2.G.6072-2
12 + 10 mm	40	39	BEB2.G.6072-1
55/2 + 55/2	39	38	BEB2.G.6072-3
55/2 + 55/2 silence	41	40	BEB2.G.6072-4
12 mm + 66/2	41	39	BEB2.G.6072-6
66/2 silence + 55/2 silence	44	42	BEB2.G.6072-5
66/2 silence + 66/2	44	43	BEB2.G.6072-7

SYNTHÈSE
GARDE-CORPS

TRAVERSE LOAD
SYNTHESIS

Remplissages (mm)	Isolant acoustique	Hauteur maximum	n° PV
Fillings (mm)	Acoustic insulation	Maximum height	Certificate
H5			
2 agglomérés 12 mm 2 chipboards 12mm	30 mm	3000 mm	BPI1.7.3022-1
2 faces 33/2 - 2 sides 33/2	–	3000 mm	BPI1.7.3022-2
1 face 33/2 - 1 side 33/2	–	3000 mm	BPI1.7.3022-3
VSA : 2 agglomérés 12 mm + 2 faces 33/2 Half glazed: 2 chipboards 12mm + 2 sides 33/2	30 mm	3000 mm	BPI1.7.3022-5
VSA : 2 agglomérés 12 mm + 1 face 33/2 Half glazed: 2 chipboards 12mm + 1 side 33/2	30 mm	3000 mm	BPI1.7.3022-4
H5T			
Double vitrage 55/2 Double glazing 55/2	JOLIA	3000 mm	BEB1.G.4095-1